

Flux Monitoring System for Turbo Generators



Key Features

- Continuous High Speed Acquisition of Rotor Flux Profile
- Ethernet and Modbus RTU Interfaces
- Standalone Operation
- Local True Color Touch LCD

Application

- Rotor Short Turn Detection of Turbo Generators

UDL-8000 - FLM

General Description

The Flux monitoring system for turbo generators is based on the **UDL-8000** data acquisition and monitoring system family for online condition monitoring of high voltage insulation systems and machines. UDL-8000 is a multi - modular system with a central CPU controller, various different signal conditioning modules and sensor interfaces (up to eight modules per controller) and application specific software packages as e.g. the package **FLM**, used for the acquisition, evaluation and monitoring of the rotor flux of turbo generators.

The rotor flux is measured by the ASC-2000 Series flux sensors installed within the airgap of the generator. The flux sensors are connected via the module **M8009** to the **UDL-8000** monitoring system. The module offers the interface for a reference sensor or reference source, two flux sensors and five 4-20mA analogue inputs for the acquisition of the machine operation condition,

The **UDL-8000** Controller offers standard interfaces as Ethernet, digital in- and outputs, relay contacts and Modbus RTU.

The Ethernet Interface is used for the communication with the analysis software running on a windows based computer the real-time data visualisation and analysis. Additionally the **UDL-8000** system can be connected to the TMS-2000 Database Server to record continuous the acquired signals (Monitoring).

Ordering Information

Order Code:

16.8000.E2.B28-0C8-2.C1.09.FLM Flux Monitoring System for 35mm DIN Rail Mounting, 24VDC

Flux Monitoring System for Turbo Generators



Technical Data

UDL-8000 - FLM

Module M8009 Specifications

Flux Sensor Input

Sampling Rate: 100kS/s
A/D Resolution: 16 bit

Input Impedance: 100kOhm, Differential
No. of Sensor Interfaces: 2

Reference Channel 1

Input Range: 0 .. 300VAC
Frequency Range: DC .. 100Hz

Galvanical Insulated: 2500VAC
Input Impedance: 10M Ohm

Reference Channel 2

Input Range: +/-30V
Frequency Range: DC .. 10kHz

Input: Differential
Input Impedance: 100 kOhm

Operation Parameters

No of Channels: 5
Input Range: 4-20mA

Input: Single Ended
Measurement Shunt: 250 Ohm

UDL-8000 Controller

Relais Contacts NO/NC: 4
Contact Rating: 240VAC

Modbus RTU slave: RS-485

Display

Dimension: 3.5"
Resolution: 320 x 240pxl

Color Depth: 24bit
Touch: Resistive

Local Results

Max, Peak, Peak-Peak, Asymmetrie
System and Alarm Status

Trend: max. 1 Year
Time Signal: 1 Revolution Data

Mechanical Dimensions

Dimensions (L x W x D): 179 x 189x152mm
Weight: 1.6kg

Protection Class: IP55
Mounting: 35mm DIN-Rail

Sparks Instruments reserves the right, without further notice, to change the product specifications and/or the information on this document to improve reliability, functions and design of this product. © 2015, Sparks Instruments, All rights reserved.

Contact

Sparks Instruments SA

Route de Montena 85, CH-1728 Rossens
Switzerland

Phone: +41 (0)26 301 30 04
Email: sales@sparksinstruments.com
Web: www.sparksinstruments.com